







ZKT_{ECO}

Model	Device Foto	Especificaciones
ZKBio610		CPU: Intel Celeron J1900 Quad-Core 2.0Ghz Display: 15" TFT LCD , 1024*768 resolución Touch Pannel: Projected Capacitive Touch Display RAM: 2G Storage: 32G SSD Customer Display: LED 8C High-difinition Digital Tube OS: Support: POS ready7/Windows Embedded 8.1 Industry/Win10 IoT Enterprise USB Port: 1*USB3.0 5*USB2.0 Power supply: 12V DC 5A adapter
ZKBio630		CPU: Intel Core i3-4005U 1.6Ghz USB Port::2*USB3.0 4*USB2.0
ZKBio650		CPU: Intel Core i5-4210U 1.7Ghz USB Port ::2*USB3.0 4*USB2.0
	12.1" 2and Customer display	
ZKBio810		15" all-in-one POS terminal with Intel Bay Trail Quad-Core processor CPU: Intel Celeron J1900 Quad-Core 2.0Ghz Display: 15" TFT LCD, 1024*768 resolución Touch Pannel: Projected Capacitive Touch Display RAM:4G Storage:64G SSD Customer Display: LED 8C High-difinition Digital Tube OS: Support: POS ready7/Windows Embedded 8.1 Industry/Win10 IoT Enterprise USB Port:1*USB3.0 5*USB2.0 Power supply: 12V DC 5A adapter Warranty: 1 year
ZKBio830		CPU: Intel Core i3-4005U 1.6Ghz USB Port::2*USB3.0 4*USB2.0
ZKBio850		CPU: Intel Core i5-4210U 1.7Ghz USB Port ::2*USB3.0 4*USB2.0

	10" 2and Customer display	
	15" 2and Customer display	
ZKBio910		<p>15" all-in-one POS terminal with Intel Bay Trail Quad-Core processor CPU: Intel Celeron J1900 Quad-Core 2.0Ghz Display: 15" TFT LCD, 1024*768 resolución Touch Pannel: Projected Capacitive Touch Display RAM:4G Storage:64G SSD Customer Display: LED 8C High-difinition Digital Tube OS: Support: POS ready7/Windows Embedded 8.1 Industry/Win10 IoT Enterprise USB Port:1*USB3.0 5*USB2.0 Power supply: 12V DC 5A adapter Warranty: 1 year</p>
ZKBio930		CPU: Intel Core i3-4005U 1.6Ghz USB Port::2*USB3.0 4*USB2.0
ZKBio950		CPU: Intel Core i5-4210U 1.7Ghz USB Port ::2*USB3.0 4*USB2.0
	10" 2and Customer display	
ZKBio910P		<p>CPU: Intel Celeron J1900 Quad-Core 2.0Ghz Display: 15" TFT LCD, 1024*768 resolución Touch Pannel: Projected Capacitive Touch Display RAM: 2G Storage: 32G SSD Built-in 80mm Thermal Printer Customer Display: LED 8C High-difinition Digital Tube OS: Support: POS ready7/Windows Embedded 8.1 Industry/Win10 IoT Enterprise USB Port: 1*USB3.0 5*USB2.0 Power supply:12V DC 5A adapter</p>
ZKBio930P		CPU: Intel Core i3-4005U 1.6Ghz USB Port::2*USB3.0 4*USB2.0
ZKBio950P		CPU: Intel Core i5-4210U 1.7Ghz USB Port ::2*USB3.0 4*USB2.0
	10" 2and Customer display	
	VFD	2*20 Line
	Barcode	2D barcode scanner for ZKBio810 series and ZKBio910 series
	iButton	For all models
	MSR	For all models
	RFID	For all models
	Fingerprint reader	silicon fingerprint reader for ZKBio810 series and ZKBio910 series
	WIFI	For ZKBio810 series and ZKBio910 series
RAM	Ram Upgrade 4Gb	From 2G update to 4G
	Ram Upgrade 8Gb	From 2G update to 8G
SSD	SSD Upgrade 64Gb	From 32G update to 64G
	SSD Upgrade 128Gb	From 32G update to 128G
	SSD Upgrade 256GB	From 32G SSD update to 256G
2.5" HDD		From 32G SSD to 320G 2.5" HDD
		From 32G SSD update to 500G HDD
		Add 320G HDD
		Add 500G HDD

<p>ZKAIO1000W</p>		<p>11.6" all-in-one Android POS terminal CPU: ARM Cortex-A53 Display: 11.6" TFT LCD , 1366*768 resolución Touch Pannel: Projected Capacitive RAM: 1GB 8GB flash memory Support: Android 6.0 or Linux Built in Printer: 58mm thermal printer WiFi : Support 802.11b/g/n Warranty: 1 years</p>
	<p>LED 8C High-difinition Digital Tube</p>	
	<p>4.3 inch Second display</p>	
<p>ZKH300</p>		<p>5.5" all-in-one Android Handheld POS terminal CPU: MTK MT6580 Display: 5.5" IPS , 1280*720 resolution Touch Pannel: Projected Capacitive RAM: 2GB EMMC: 16GB OS Support: Android 5.1/7.0 Built in Printer: 58mm thermal printer WiFi : Support 802.11b/g/n Rear Camera : 5 Mega-pixel Support 4G communication</p>
<p>ZKAIO1500</p>		<p>10.1" all-in-one Android Tablet POS terminal CPU: Allwinner A64 quad core processor Display : 10.1 inch IPS screen, 1280*800 resolution Touch Pannel : Projected Capacitive RAM: 2GB ROM: 8GB OS Support : Android 6.0 WiFi : Support 802.11b/g/n Front Camera : 200W pixel</p>
<p>ProMerc-100</p>		<p>11.6" Android consumption of machine CPU: RK3288 Display: 11.6" TFT LCD, 1366*768 resolution; 11.6" second display Touch Pannel: Projected Capacitive RAM: 2GB EMMC: 8GB OS Support: Android 6.0 Support ID/MF card WiFi : Support 802.11b/g/n Rear Camera : 2 Mega-pixels</p>