







**ZKT<sub>ECCO</sub>**

Model	Device Foto	Especificaciones
Cash Drawer		
ZKC0408		Casing :Steel construction with cold-pressed front Lock :3 positions key lock Cash Tray : <b>4B8C</b> (4 bill,8 coin) with adjustable dividers Dimensions :410W*415D*100H(mm) Port :RJ11 12V/24V Weight :Gross:6.3kg Net:5.6kg
ZKC0508		Casing :Steel construction with cold-pressed front Lock :3 positions key lock Cash Tray : <b>5B8C</b> (5 bill,8 coin) with adjustable dividers Dimensions :410W*415D*100H(mm) Port :RJ11 12V/24V Weight :Gross:6.4kg Net:5.8kg
ZKC0704		Casing :Steel construction with cold-pressed front Lock :3 positions key lock Cash Tray : <b>7B4C</b> (7bill,4 coin) with adjustable dividers Dimensions :405W*420D*95H(mm) Port :RJ11 12/24V Weight :Net:5.6kg





Thermal Printer		
ZKP5803		58mm Thermal Printer Print speed:90mm/s TPH:100Km Output:DC 12V/3A <b>Interface: USB (Standard),</b> Dimension:215*110*136mm
ZKP5801		58mm Thermal Printer <span style="float: right;">Print</span> speed:90mm/s TPH:100Km Output:DC 12V/3A <b>Interface: USB (Standard),</b> Dimension:215*110*136mm
ZKP5802		58mm Thermal Printer <span style="float: right;">Print</span> speed:90mm/s TPH:100Km Output:DC 12V/3A <b>Interface: USB (Standard),</b> Dimension:215*110*136mm
ZKP5808		58mm PortableThermal Printer <span style="float: right;">Print</span> speed:90mm/s TPH:100Km Output:DC 9V/1.5A Built-in battery:7.4VDC/1500mAh <b>Interface: USB+RS232+Bluetooth4.0(USB cable is standard)</b>
		Funda protectora para ZKP580

ZKP8001		<p>80mm Thermal Printer with auto-cutter          Print speed :300mm/s      TPH:100Km          Output :DC 24V/2.5A          Interface :<b>USB+RS232+LAN</b>          Dimension :190*145*145mm          Options :LAN(-3USD) RS232 cable for connecting with time attendance device</p>
ZKP8003		<p>80mm Portable Thermal Printer    Print speed :90mm/s    TPH:100Km          Output :DC 9V/1.5A          Built-in battery :7.4VDC/2000mAh          Interface: <b>USB+RS232+Bluetooth4.0(USB cable is standard)</b></p>
ZKP8005		<p>80mm Desktop Thermal Printer with auto-cutter          Print speed: <b>200mm/s</b>          TPH:100Km          Output: DC 24V/2.5A          Interface: <b>USB</b>          Dimension: 192*145*133mm</p>
ZKP8006		<p>Desktop Label Printer with auto-cutter          Print speed: 160mm/s          Print Width: 100mm          Output:DC 24V/2.5A          Interface: USB          Dimension: 180*115*107mm</p>
ZKP8008		<p>80mm Desktop Thermal Printer with auto-cutter          Print speed: <b>200mm/s</b>          TPH:100Km          Output: DC 24V/2.5A          Interface: <b>USB</b>          Dimension: 192*145*133mm</p>
Thermal Printer Paper		<p>width57*diam45mm, 100 rolls/box, 70gr, 12 meters long</p> <p>width80*diam45mm, 100 rolls/box, 70gr, 12 meters long</p> <p>width80*diam74mm, 50 rolls/box, 70gr, 41 meters long</p> <p>width80*diam80mm, 50 rolls/box, 65gr, 52 meters long</p>

Barcode Scanner

ZKB101		1D Laser Barcode Scanner
ZKB102		1D Red Light Barcode Scanner
ZKB103		1D Wireless Laser Barcode Scanner
ZKB104		1D Wireless Red Light Barcode Scanner
ZKB105		1D Wireless Laser Barcode Scanner with Stand
ZKB106		1D Wireless Red Light Barcode Scanner with stand

ZKB109		1D Barcode Scanner Laser, LED 650nm 20 lines scanning Interface: RS232, USB Decode Error Rate: 1/5 million
ZKB201		2D Barcode Scanner
ZKB202		2D Wireless Barcode Scanner
ZKB203		2D Wireless Barcode Scanner with Stand. 100,000 códigos de productos básicos (16 MB). IP54
ZKB205		2D Laser Embedded Module
ZKB209		2D Barcode Scanner Platform, Multiline scanning
ZKBS		The stand for hand-held scanner

Touch Monitor		
ZKD1502R		15" TFT LCD panel 1024*768 Domestic Resistive Touch Screen Folding Base 12V 3A power supply      Projected Capacitive Screen:+20USD
ZKD1502C		Projected Capacitive Screen
ZKD1702R		17" TFT LCD panel 1280*1024 Domestic Resistive Touch Screen Folding Base 12V 3A power supply      Projected Capacitive Screen:+25USD
ZKD1702C		Projected Capacitive Screen
ZK-VFD01		Vacuum Fluorescent Display 2lines*20 Characters Interface:USB port
ZK-VFD02		Vacuum Fluorescent Display 2lines*20 Characters Interface:USB port
ZK-MSR		USB Magnetic Card Reader for POS